




aerospace
climate control
electromechanical
filtration
fluid & gas handling
hydraulics
pneumatics
process control
sealing & shielding



Directional Control Valves

Series VA13 and VA15

3- and 5-port valves. G1/8

Catalogue PDE2617TCUK February 2016



ENGINEERING YOUR SUCCESS.

Directional control valves

Working medium, air quality

Working medium: Dry, filtered compressed air to ISO 8573-1 class 3.4.3.

Recommended air quality

For best possible service life and trouble free operation, ISO 8573-1 quality class 3.4.3 should be used. This means 5µm filter (standard filter) dew point +3°C for indoor operation (a lower dew point should be selected for outdoor operation) and oil concentration 1.0 mg oil/m³, which is what a standard compressor with a standard filter gives.

Compact installation dimensions - flexible installation



The VA13/15 valve range consists of spool valves of extremely robust design, incorporating a wide range of manual, mechanical and pilot-operated actuators.

Rust and corrosion resistant designs.

The valve bodies and caps are made of brass. Stainless steel is used in the spools and the mechanical actuating devices. Versions intended for panel mounting have chromium-plated steel actuators and panel bezels.

Mobile applications




The robust design, coupled with good corrosion resistance, makes the valves suitable for a wide range of applications. Manually operated valves are suitable for industrial and transport applications. The stable and ergonomically designed actuators make the valves easy to operate even with heavy working gloves.

ISO 8573-1 quality classes

Quality class	Pollution		Water max. press. dew point (°C)	Oil max. concentration (mg/m ³)
	particle size (µm)	max. concentration (mg/m ³)		
1	0,1	0,1	-70	0,01
2	1	1	-40	0,1
3	5	5	-20	1,0
4	15	8	+3	5,0
5	40	10	+7	25
6	-	-	+10	-

High reliability




Valves easily comply with the requirements for component reliability in accordance with EU Machinery Directive standards EN292-2 and EN983.

The VA valves have few moving parts combined with short spool movement, these features combine to give valves having high reliability and long service life. The valves are designed for use with or without supplementary lubrication.

Maintenance

When maintenance is required repair kits containing replacement seals are available. See page 15

Directional control valves



Ordering example

VA13-HIS4

Valve type, VA _____

Valve size 1 = G1/8 _____

Number of ports, 3 or 5 _____

Type of actuation _____

Type of return _____

Type of installation _____

4 = panel mounted _____



Products specially suitable for the transport industry.


Directional control valves

Installation

Correctly mounted valves require only a minimum of maintenance. For maximum life, follow the instructions with regard to actuation directions, actuation speeds, angles and adjustments.

Panel mounting

Mount the valves in a 40,5 mm diameter hole (thread M40 x 1,5). The panel-mounting collars have a flange on the front of the panel and a retaining nut behind the panel, for simple installation and clean and attractive appearance.




Fitting adjustable roller actuators

The rest position of the actuating arm can be arranged at any required angle on the actuator shaft (360°).


The length of the arm is adjustable, and it can also be rotated through 180°. Note, however, that the roller must always be parallel to the valve body.

The arm can also be positioned on the other side of the valve by removing the actuating mechanism, turning it through 180° and reassembling it.




Actuation

Maximum actuation distance (X), i.e. the maximum spool stroke length, is 4 mm. Valves are fully open after 3,5 mm travel. Type UW toggle cam actuators permit a vertical motion in toggle direction of up to 10 mm.



Actuation speed as a function of actuation angle

Optimum valve life will be obtained if the shape of actuation cams is matched to the method of actuation employed. The principle is that the higher the speed of the actuating motion, the smaller the incident angle. The characteristic curve shown here plots the incident angle against speed of the actuating stroke.



Actuation

Maximum actuation distance, the maximum spool stroke length is 7.6 mm.

Actuation by adjustable roller

Actuation can be arranged in both directions if the arm is set as shown above. The arm needs to be moved through only 5° to make the valve change over, although a travel range of up to 90° can be accepted.

Material specifications

Valve bodys, end covers,	Brass
spring guides	Polished stainless steel
Spools	Nitrile rubber
Seals	Zinc plated steel
Screws, nuts, washers	Steel
Balls	Acetal plastic
Push-buttons, knobs	Chrome-plated steel
Levers	Phosphatized cast-iron
Pedals	Hardened stainless steel
I-plunger	Acetal plastic
Rollers	















IMPORTANT

Before servicing, make sure that the valve is depressurised. Disconnect the primary air hose to ensure that the air supply is safely interrupted before removing valves.

Data

Working temperature: -20 °C to +70 °C
 Working pressure: max 10 bar
 Flow (acc. to ISO 6358)
 C: 0,9 NI/s, bar
 Qn (P1=6 bar, Δp=1 bar): 3,6 l/s
 Qmax: 6,3 l/s
 Cv: 0,21

Symbol	Actuator	Return	Mounting	Changeover force at 6 bar	Weight kg	Order code
 	Push-button Red	Spring	Panel mounted	32,5 N	0,37	VA13-HIS4
	Push-button Black	Spring	Panel mounted	32,5 N	0,37	VA13-HIS4A06*
 	Push-button Red	Air signal	Panel mounted	6 N**	0,37	VA13-HIA4
 	Hand lever Held in two positions	Hand lever	Panel mounted	8 N	0,52	VA13-HB24
			Side mounted	8 N	0,35	VA13-HB2
 	Knob Red Two positions	Knob	Panel mounted	3 N	0,48	VA13-KL24
			Side mounted	3 N	0,31	VA13-KL2
 	Knob Red	Spring	Panel mounted	31,5 N	0,49	VA13-KS4
			Side mounted	31,5 N	0,32	VA13-KS
 	Knob Red Two positions	Knob/ Air signal	Panel mounted	6 N**	0,49	VA13-KL2A4
			Side mounted	6 N**	0,33	VA13-KL2A

* Panel holder in black anodized aluminium.





















** Without signal pressure. Signal pressure min 3 bar at 6 bar supply pressure.



All VA13 valves (except VA13-WGR and VA13-RWG) can be connected either as normally closed 3/2 valve (NC) or normally open 3/2 valve (NO) as required, by connecting the primary air supply to Port 1 or Port 3.

Data

Working temperature:	-20 °C to +70 °C
Working pressure:	max 10 bar
Flow (acc. to ISO 6358)	
C:	0,9 Nl/s, bar
Qn (P1=6 bar, Δp=1 bar):	3,6 l/s
Qmax:	6,3 l/s
Cv:	0,21




	Symbol	Actuator	Return	Mounting	Changeover force at 6 bar	Weight kg	Order code
		Push-button Red	Spring	Panel mounted	34,5 N	0,46	VA15-HIS4
		Hand lever Held in two positions	Hand lever	Panel mounted	9 N	0,63	VA15-HB24
				Side mounted	9 N	0,45	VA15-HB2
		Hand lever Held in three positions	Hand lever	Panel mounted Closed centre position	9 N	0,63	VA15-HB34
		Hand lever Held in three positions	Hand lever	Panel mounted Exhausted centre position	9 N	0,63	VA15-XHB34
		Hand lever Three positions self-centring	Hand lever	Panel mounted Closed centre position	9 N	0,63	VA15-HC4
		Hand lever Three positions self-centring	Hand lever	Panel mounted Exhausted centre position	9 N	0,63	VA15-XHC4
		Knob Red Two positions	Knob	Panel mounted	5 N	0,58	VA15-KL24
				Side mounted	5 N	0,42	VA15-KL2
		Knob Red	Spring	Panel mounted	34,5 N	0,60	VA15-KS4
		Knob Red Two positions	Knob/Air signal	Panel mounted	8 N*	0,61	VA15-KL2A4

*Without signal pressure. Signal pressure min 3 bar at 6 bar supply pressure.



Data

Working temperature:	-20 °C to +70 °C
Working pressure:	max 10 bar
Flow (acc. to ISO 6358)	
C:	0,9 NI/s, bar
Qn (P1=6 bar, Δp=1 bar):	3,6 l/s
Qmax:	6,3 l/s
Cv:	0,21

VA13

















Symbol	Actuator	Return	Mounting	Signal pressure min, bar at 6 bar actu./return	Weight Kg	Order code
	Air signal	Air signal	Side mounted	3/3	0,33	VA13-AA
	Air signal	Spring	Side mounted	4/-	0,32	VA13-AS
	Air signal with priority	Air signal	Side mounted	3/4	0,32	VA13-ADA

VA15



Symbol	Actuator	Return	Mounting	Signal pressure min, bar at 6 bar actu./return	Weight Kg	Order code
	Air signal	Air signal	Side mounted	3/3	0,33	VA15-AA
	Air signal	Spring	Side mounted	4/-	0,32	VA15-AS
	Air signal with priority	Air signal	Side mounted	3/4	0,32	VA15-ADA

Data

Working temperature: -20 °C to +70 °C
 Working pressure: max 10 bar
 max 8 bar for WGR and RWG
 Flow (acc. to ISO 6358)
 C: 0,9 NI/s, bar
 Qn (P1=6 bar, Δp=1 bar): 3,6 l/s
 Qmax: 6,3 l/s
 Cv: 0,21

	Symbol	Actuator	Return	Mounting	Changeover force at 6 bar	Weight kg	Order code
		Plunger	Spring	Side mounted	32,5 N	0,30	VA13-IS
		Plunger Two positions	Plunger	Side mounted	3 N	0,30	VA13-II
		Plunger	Air signal	Side mounted	6 N*	0,30	VA13-IA
		Roller one way trip	Spring	Side mounted	20,5 N	0,33	VA13-UWS
		Roller	Spring	Side mounted	32,5 N	0,33	VA13-WS
		Roller on an arm	Internal air min 4 bar	Side mounted Normally closed	0,6 N min	0,41	VA13-WGR
		Roller on an arm	Internal air min 4 bar	Side mounted Normally open	0,6 N min	0,41	VA13-RWG
		Roller	Spring	Side mounted		0,41	VA13-LRS

* Without signal pressure. Signal pressure min 3 bar at 6 bar supply pressure.












All VA13 valves (except VA13-WGR and VA13-RWG) can be connected either as normally closed 3/2 valve (NC) or normally open 3/2 valve (NO) as required, by connecting the primary air supply to Port 1 or Port 3.


Data

Working temperature: -20 °C to +70 °C
 Working pressure: max 10 bar
 max 8 bar for WGR


Flow (acc. to ISO 6358)
 C: 0,9 NI/s, bar
 Qn (P1=6 bar, Δp=1 bar): 3,6 l/s
 Qmax: 6,3 l/s
 Cv: 0,21

	Symbol	Actuator	Return	Mounting	Changeover force at 6 bar	Weight kg	Order code
		Plunger	Spring	Side mounted	34,5 N	0,40	VA15-IS
		Plunger Two positions	Plunger	Side mounted	5 N	0,40	VA15-II
		Roller one way trip	Spring	Side mounted	21,6 N	0,43	VA15-UWS
		Roller	Spring	Side mounted	34,5 N	0,44	VA15-WS
		Roller on an arm	Internal air min 4 bar	Side mounted	0,6 N min	0,46	VA15-WGR
		Roller	Spring	Side mounted		0,46	VA15-LRS



Dimensions




Dimensions




Dimensions



Dimensions




Dimensions




Accessories

Sintered bronze series





Port	Order code	Pack Qty
G1/8	9090050700	1

Male straight connectors - Parallel thread



Tube Ø1	Thread B	Order code	Box Qty
4	1/8	F4PMB4-1/8	20
6	1/8	F4PMB6-1/8	30
8	1/8	F4PB8-1/8	40

Service and Replacement Parts



VA Series Heavy Duty Valves

Order code	Repair Kit
9128674100	Body seals (6 pcs. 'O' Ring)



Important !

Before carrying out any service work, ensure that the valve and manifold have been vented. Remove the primary supply air hose to ensure total disconnection of the air supply before dismantling valves or blank connection blocks.



NB !

All technical data in this catalogue is typical only. The air quality is decisive for the valve life: see ISO 8573.



WARNING

FAILURE OR IMPROPER SELECTION OR IMPROPER USE OF THE PRODUCTS AND/OR SYSTEMS DESCRIBED HEREIN OR RELATED ITEMS CAN CAUSE DEATH, PERSONAL INJURY AND PROPERTY DAMAGE.

This document and other information from Parker Hannifin Corporation, its subsidiaries and authorized distributors provide product and/or system options for further investigation by users having technical expertise. It is important that you analyze all aspects of your application and review the information concerning the product or system in the current product catalog. Due to the variety of operating conditions and applications for these products or systems, the user, through its own analysis and testing, is solely responsible for making the final selection of the products and systems and assuring that all performance, safety and warning requirements of the application are met. The products described herein, including without limitation, product features, specifications, designs, availability and pricing, are subject to change by Parker Hannifin Corporation and its subsidiaries at any time without notice.

SALE CONDITIONS

The items described in this document are available for sale by Parker Hannifin Corporation, its subsidiaries or its authorized distributors. Any sale contract entered into by Parker will be governed by the provisions stated in Parker's standard terms and conditions of sale (copy available upon request).

Parker Worldwide

Europe, Middle East, Africa

AE – United Arab Emirates,
Dubai

Tel: +971 4 8127100
parker.me@parker.com

AT – Austria, Wiener Neustadt

Tel: +43 (0)2622 23501-0
parker.austria@parker.com

AT – Eastern Europe, Wiener
Neustadt

Tel: +43 (0)2622 23501 900
parker.easteurope@parker.com

AZ – Azerbaijan, Baku

Tel: +994 50 2233 458
parker.azerbaijan@parker.com

BE/LU – Belgium, Nivelles

Tel: +32 (0)67 280 900
parker.belgium@parker.com

BG – Bulgaria, Sofia

Tel: +359 2 980 1344
parker.bulgaria@parker.com

BY – Belarus, Minsk

Tel: +375 17 209 9399
parker.belarus@parker.com

CH – Switzerland, Etoy

Tel: +41 (0)21 821 87 00
parker.switzerland@parker.com

CZ – Czech Republic, Klecany

Tel: +420 284 083 111
parker.czechrepublic@parker.com

DE – Germany, Kaarst

Tel: +49 (0)2131 4016 0
parker.germany@parker.com

DK – Denmark, Ballerup

Tel: +45 43 56 04 00
parker.denmark@parker.com

ES – Spain, Madrid

Tel: +34 902 330 001
parker.spain@parker.com

FI – Finland, Vantaa

Tel: +358 (0)20 753 2500
parker.finland@parker.com

FR – France, Contamine s/Arve

Tel: +33 (0)4 50 25 80 25
parker.france@parker.com

GR – Greece, Athens

Tel: +30 210 933 6450
parker.greece@parker.com

HU – Hungary, Budaörs

Tel: +36 23 885 470
parker.hungary@parker.com

IE – Ireland, Dublin

Tel: +353 (0)1 466 6370
parker.ireland@parker.com

IT – Italy, Corsico (MI)

Tel: +39 02 45 19 21
parker.italy@parker.com

KZ – Kazakhstan, Almaty

Tel: +7 7273 561 000
parker.easteurope@parker.com

NL – The Netherlands, Oldenzaal

Tel: +31 (0)541 585 000
parker.nl@parker.com

NO – Norway, Asker

Tel: +47 66 75 34 00
parker.norway@parker.com

PL – Poland, Warsaw

Tel: +48 (0)22 573 24 00
parker.poland@parker.com

PT – Portugal, Leca da Palmeira

Tel: +351 22 999 7360
parker.portugal@parker.com

RO – Romania, Bucharest

Tel: +40 21 252 1382
parker.romania@parker.com

RU – Russia, Moscow

Tel: +7 495 645-2156
parker.russia@parker.com

SE – Sweden, Spånga

Tel: +46 (0)8 59 79 50 00
parker.sweden@parker.com

SL – Slovenia, Novo Mesto

Tel: +386 7 337 6650
parker.slovenia@parker.com

TR – Turkey, Istanbul

Tel: +90 216 4997081
parker.turkey@parker.com

UA – Ukraine, Kiev

Tel: +380 44 494 2731
parker.poland@parker.com

UK – United Kingdom, Warwick

Tel: +44 (0)1926 317 878
parker.uk@parker.com

ZA – South Africa, Kempton Park

Tel: +27 (0)11 961 0700
parker.southafrica@parker.com

North America

CA – Canada, Milton, Ontario

Tel: +1 905 693 3000

US – USA, Cleveland

Tel: +1 216 896 3000

Asia Pacific

AU – Australia, Castle Hill

Tel: +61 (0)2-9634 7777

CN – China, Shanghai

Tel: +86 21 2899 5000

HK – Hong Kong

Tel: +852 2428 8008

IN – India, Mumbai

Tel: +91 22 6513 7081-85

JP – Japan, Tokyo

Tel: +81 (0)3 6408 3901

KR – South Korea, Seoul

Tel: +82 2 559 0400

MY – Malaysia, Shah Alam

Tel: +60 3 7849 0800

NZ – New Zealand, Mt Wellington

Tel: +64 9 574 1744

SG – Singapore

Tel: +65 6887 6300

TH – Thailand, Bangkok

Tel: +662 186 7000

TW – Taiwan, Taipei

Tel: +886 2 2298 8987

South America

AR – Argentina, Buenos Aires

Tel: +54 3327 44 4129

BR – Brazil, Sao Jose dos Campos

Tel: +55 12 4009 3500

CL – Chile, Santiago

Tel: +562 2303 9640

MX – Mexico, Toluca

Tel: +52 72 2275 4200

European Product Information Centre

Free phone: 00 800 27 27 5374

(from AT, BE, CH, CZ, DE, DK, EE, ES, FI,
FR, IE, IL, IS, IT, LU, MT, NL, NO, PL, PT, RU,
SE, SK, UK, ZA)

Parker Hannifin Ltd.

Tachbrook Park Drive
Tachbrook Park, Warwick CV34 6TU
United Kingdom

Tel.: +44 (0) 1926 317 878

Fax: +44 (0) 1926 317 855

parker.uk@parker.com

www.parker.com

